## NSN 5930-00-577-0163

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-577-0163

Overall Length:
5.375 inches
Overall Height:
2.875 inches
Overall Width:
4.875 inches
Body Length:
2.500 inches
Body Width:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.562 inches
Longest Horizontal Distance Between Mounting Centers:
1.750 inches
Intermediate Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
160.00 pounds per square inch
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Obtuse triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
Contact Load Current Nating.

## **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

## **Contact Adjustment Range:**

+5.00/+75.00 actuation point pounds per square inch and +5.00/+75.00 deactuation point pounds per square inch

## NSN 5930-00-577-0163

Pressure Switch - Page 2 of 2



Contact	Adjustmen	t Type:
		naint aar

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:** 

550.0 ac at sea level first voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0