

View Online at <https://aerobasegroup.com/nsn/5930-00-577-0317>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.213 inches single mounting facility

**Width Between Flats:**

0.093 inches single actuator

**Overall Length:**

1.904 inches

**Flat Height:**

0.186 inches single actuator and 0.188 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.516 inches single actuator

**Overall Diameter:**

1.938 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-40.0/+65.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, parallel flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

**Special Features:**

Shat tapped with no. 6-32 thd 0.312 in. Deep

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0