NSN 5930-00-577-0573

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-577-0573

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.359 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Cvn 68 class auxiliary system, forrestal class cv, mars class cvn, nimitz class cvn
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
1.5 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:

7.0 ounces

NSN 5930-00-577-0573

Sensitive Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Special Features:
Weapon system essential
Terminal Type And Quantity:
5 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No