

View Online at <https://aerobasegroup.com/nsn/5930-00-577-2284>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.876 inches

Overall Height:

1.312 inches

Overall Width:

1.250 inches

First Flat Length:

0.319 inches 1st actuator

Flat Height:

0.219 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.813 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 1st actuator

Shaft Type:

Round, hollowed, flatted 1st actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0