

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2000>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.572 inches and 0.630 inches

**Body Length:**

Between 0.807 inches and 0.817 inches

**Body Width:**

Between 0.422 inches and 0.454 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.053 inches and 0.063 inches

**Actuator Length:**

Between 0.093 inches and 0.125 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.546 inches and 0.578 inches

**Actuator Free Position Height:**

Between 0.0570 inches and 0.067 inches

**Actuator Adapter Style:**

Pushbutton

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

32.0 ounces

**Actuator Movement:**

Between 0.004 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0