

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2000>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.572 inches and 0.630 inches

Body Length:

Between 0.807 inches and 0.817 inches

Body Width:

Between 0.422 inches and 0.454 inches

Unthreaded Mounting Hole Diameter:

Between 0.053 inches and 0.063 inches

Actuator Length:

Between 0.093 inches and 0.125 inches

Actuator Style:

Leaf

Actuator Width:

Between 0.546 inches and 0.578 inches

Actuator Free Position Height:

Between 0.0570 inches and 0.067 inches

Actuator Adapter Style:

Pushbutton

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

Between 0.004 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0