

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2197>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.469 inches

Body Length:

0.844 inches

Body Width:

0.719 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.688 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

125.0 ac and 250.0 dc

Mounting Surface To Terminal End Distance:

0.969 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0