

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2500>

Thread Class:

2b single mounting facility

Overall Length:

9.250 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Shaft Diameter:

0.249 inches single actuator and 0.250 inches single actuator

Shaft Length:

2.000 inches single actuator

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.376 inches single mounting facility

Intermediate Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

16 each section front

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Four position parallelogram single mounting facility

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0