

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2500>

**Thread Class:**

2b single mounting facility

**Overall Length:**

9.250 inches

**Overall Height:**

2.250 inches

**Overall Width:**

2.250 inches

**Shaft Diameter:**

0.249 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

2.000 inches single actuator

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

0.376 inches single mounting facility

**Intermediate Horizontal Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.500 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

16 each section front

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Mounting Facility Pattern:**

Four position parallelogram single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0