

View Online at <https://aerobasegroup.com/nsn/5930-00-578-2659>

Thread Length:

0.406 inches single pressure connection

Overall Length:

1.938 inches

Outside Diameter:

0.125 inches single connection

Overall Height:

4.000 inches

Body Length:

1.938 inches

Pressure Switch Type:

Differential

Mounting Method:

Inlet connection

Contact Action Stimulus:

Decrease

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

100.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+200.00 actuation point pounds per square inch gage and +100.00/+200.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point serrated nut

Contact Stimulus Rating:

120.00 actuation point pounds per square inch gage and 125.00 deactuation point pounds per square inch gage and 5.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

150.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0