

NSN 5930-00-578-2735 Sensitive Switch - Page 1 of 2	AUT
View Online at https://aerobasegroup.com/nsn/5930-00-578-2735	
Body Style:	
Hole mounted	
Hazardous Locations/environmental Protection:	
Dustproof	
Overall Length:	
2.406 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
Between 0.998 inches and 1.002 inches	
Overall Width:	
0.688 inches	
Body Length:	
1.938 inches	
Body Width:	
0.688 inches	
Body Height:	
0.781 inches	
Case Material:	

Plastic

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.110 inches and 1.140 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.188 inches

Maximum Voltage Rating In Volts:

600.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

Between 6.0 ounces and 12.0 ounces

Actuator Movement:

Between 0.062 pretravel inches and 0.031 overtravel inches and 0.032 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 2.000 amperes resistive ac

NSN 5930-00-578-2735

Sensitive Switch - Page 2 of 2



Special Features:
Insulator included
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0