## NSN 5930-00-578-3133

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-578-3133

**Thread Class:** 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.438 inches **Overall Height:** 1.250 inches **Overall Width:** 0.906 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.109 inches single actuator **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.594 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 2 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-578-3133

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and wipers silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0