# NSN 5930-00-578-3301

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-578-3301

Overall Height:				
3.500 inches				
Overall Width:				
5.250 inches				
First Flat Length:				
0.500 inches single actuator				
Flat Height:				
0.310 inches single actuator				
Shaft Diameter:				
0.375 inches single actuator				
Shaft Length:				
1.188 inches single actuator				
Individual Section Quantity:				
6				
Knob Manufacturer Code:				
80064				
Knob Manufacturer Part Number:				
9000s6202-74089-3				
Longest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Features Provided:				
Actuator knob				
Thready Qty Per Inch (tpi):				
24 single mounting facility				
Thread Size:				
0.190 inches single mounting facility				
Contact Voltage Rating In Volts:				
450.0 ac at sea level				
Mounting Facility Pattern:				
Four position rectangular single mounting facility				
Switch Actuator Indexing Position Quantity:				
4 single actuator				
Shaft Type:				
Round, flatted, threaded hole single actuator				
Terminal Type:				

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section front

## NSN 5930-00-578-3301

Rotary Switch - Page 2 of 2



Switch	Actuator	<b>Positioning</b>	Increment:
--------	----------	--------------------	------------

90.0 degrees single actuator

### **Contact Load Current Rating:**

30.0 amperes resistive load dc at sea level

#### **Special Features:**

Terminals relocated from back to side connected

#### **Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc single mounting facility

#### **Specification Or Standard:**

3sr class

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0