NSN 5930-00-578-3951

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-578-3951

Here I and a second a transfer of Device de la
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
13.000 inches
Overall Height:
7.250 inches
Overall Width:
8.125 inches
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
5
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-73075
Longest Horizontal Distance Between Mounting Centers:
5.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
8 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment

45.0 degrees single actuator

NSN 5930-00-578-3951

Rotary Switch - Page 2 of 2



	Switch	Actuator	Stop	Device	Type:
--	--------	----------	------	---------------	-------

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0