

View Online at <https://aerobasegroup.com/nsn/5930-00-578-4037>

Thread Length:

0.625 inches single pressure connection

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

3.000 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.814 inches

Overall Diameter:

2.375 inches

Pressure Switch Type:

Differential

Width Across Flats:

Between 0.847 inches and 0.875 inches

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Decrease

Proof Pressure:

550.00 pounds per square inch gage

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2.40 actuation point pounds per square inch gage and 3.30 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0