

View Online at <https://aerobasegroup.com/nsn/5930-00-578-6955>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

Between 1.922 inches and 1.954 inches

**Overall Height:**

Between 1.859 inches and 1.891 inches

**Overall Width:**

Between 1.546 inches and 1.578 inches

**First Flat Length:**

0.422 inches single actuator and 0.454 inches single actuator

**Flat Height:**

0.202 inches single actuator and 0.234 inches single actuator

**Shaft Diameter:**

0.234 inches single actuator and 0.266 inches single actuator

**Shaft Length:**

0.734 inches single actuator and 0.766 inches single actuator

**Nonturn Device Radius:**

0.515 inches at 12: 00 o'clock and 0.547 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

6 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0