NSN 5930-00-578-6965

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5930-00-576-6965
Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
6.750 inches
Overall Width:
9.500 inches
First Flat Length:
0.625 inches single actuator
Flat Height:
0.500 inches single actuator
Shaft Diameter:
0.625 inches single actuator
Shaft Length:
0.875 inches single actuator
Unthreaded Mounting Hole Diameter:
0.562 inches single mounting facility
Individual Section Quantity:
5
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
500.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment

90.0 degrees single actuator

NSN 5930-00-578-6965

Rotary Switch - Page 2 of 2



Contact	l nad	Current	Rating	
Cullact	Luau	Current	Naumu	

200.0 amperes resistive load ac at sea level

Special Features:

Round, flatted, threaded hole and pin type shaft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0