

View Online at <https://aerobasegroup.com/nsn/5930-00-578-6965>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

6.750 inches

Overall Width:

9.500 inches

First Flat Length:

0.625 inches single actuator

Flat Height:

0.500 inches single actuator

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

0.875 inches single actuator

Unthreaded Mounting Hole Diameter:

0.562 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

5.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Special Features:

Round, flatted, threaded hole and pin type shaft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0