Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-578-9778

| Hazardous Locations/environmental Protection: | |
|--|--|
| Dustproof | |
| Overall Length: | |
| 5.376 inches | |
| Overall Height: | |
| 2.906 inches | |
| Overall Width: | |
| 2.812 inches | |
| Unthreaded Mounting Hole Diameter: | |
| 0.221 inches single mounting facility | |
| Individual Section Quantity: | |
| 2 | |
| Knob Manufacturer Code: | |
| 82121 | |
| Knob Manufacturer Part Number: | |
| 3 | |
| Longest Horizontal Distance Between Mounting Centers: | |
| 2.000 inches single mounting facility | |
| Shortest Horizontal Distance Between Mounting Centers: | |
| 1.000 inches single mounting facility | |
| Longest Vertical Distance Between Mounting Centers: | |
| 2.188 inches single mounting facility | |
| Switch Contact Basic Design: | |
| Nonpile-up symmetrical | |
| Pole Quantity: | |
| 1 each section rear | |
| Throw Quantity: | |
| 3 each section rear | |
| Mounting Method: | |
| Unthreaded hole single mounting facility | |
| Features Provided: | |
| Actuator knob | |
| Contact Voltage Rating In Volts: | |
| 600.0 ac at sea level | |
| Mounting Facility Pattern: | |
| sosceles triangle single mounting facility | |
| Switch Actuator Indexing Position Quantity: | |
| 4 single actuator | |
| Ferminal Type: | |
| Tab w/screw | |
| | |
| Contact Switching Action: | |
| Breaks before makes each section rear | |

NSN 5930-00-578-9778

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 20.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0