## NSN 5930-00-578-9790

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-578-9790

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Width:
2.310 inches
Actuator Length:
2.250 inches
Actuator Style:
Roller arm
Actuator Height:
2.030 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.100 inches
Housing Length:
4.950 inches
Housing Width:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.220 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.810 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 two circuit, two positions momentary single switch unit
Switch Release Force:
40.0 inch-ounces
Switch Actuating Force:
190.0 inch-ounces
Actuator Movement:
17.0 pretravel degrees and 80.0 overtravel degrees and 11.0 differential degrees

15.000 amperes resistive ac

**Contact Load Current Rating At Maximum Rated Voltage:** 

## NSN 5930-00-578-9790

Sensitive Switch - Page 2 of 2



Special	Features:
---------	-----------

Cw operation 3/lever no aj w/back mtg plate style 2 lever may be positioned within a 220 degrees range

**Terminal Type And Quantity:** 

8 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0