NSN 5930-00-578-9792

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

Dustproof and watertight



View Online at https://aerobasegroup.com/nsn/5930-00-578-9792

Overall Width:
2.312 inches
Actuator Length:
1.250 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.062 inches
Housing Length:
4.953 inches
Housing Width:
2.312 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
40.0 inch-ounces
Switch Actuating Force:
125.0 inch-ounces
Actuator Movement:
Between 70.0 pretravel degrees and 70.0 overtravel degrees and 10.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes inductive ac
Special Features:
Ccwoperation lever may be positioned within 220.0 degrees range
Terminal Type And Quantity:
6 screw

NSN 5930-00-578-9792

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0