

View Online at <https://aerobasegroup.com/nsn/5930-00-578-9817>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.250 inches and 1.312 inches

Body Diameter:

Between 0.328 inches and 0.360 inches

Bushing Length:

Between 0.265 inches and 0.297 inches

Body Length:

Between 0.500 inches and 0.532 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.109 inches and 0.141 inches

Actuator Height:

Between 0.593 inches and 0.625 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.500 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0