

View Online at <https://aerobasegroup.com/nsn/5930-00-579-0888>

Overall Length:

1.656 inches

Overall Height:

2.819 inches

Overall Width:

1.250 inches

Mounting Slot Width:

0.140 inches

Body Length:

1.531 inches

Distance Between Mounting Facility Centers:

Between 2.187 inches and 3.781 inches

Capillary Tube Length:

72.0 inches

Tempurature Sensing Element Type:

Capillary tube

Operating Tempurature Rating:

75.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

20.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+35.00/+55.00 actuation point degrees fahrenheit and +34.00/+58.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0