NSN 5930-00-581-3425

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Height: 22.875 inches Overall Width: 6.312 inches Shaft Length:



View Online at https://aerobasegroup.com/nsn/5930-00-581-3425

1.094 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
25
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-73075pc1
Longest Horizontal Distance Between Mounting Centers:
7.875 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
4.125 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
8 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.248 inches single actuator
Terminal Type:
Tab w/screw

NSN 5930-00-581-3425

Rotary Switch - Page 2 of 2

A052b0



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level
Special Features:
Illuminated
Test Data Document:
80064-9s5564l drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Specification Or Standard:
2jr style
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: