NSN 5930-00-581-3788

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-581-3788

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

6.562 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

10

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

74421-58

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

7 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

NSN 5930-00-581-3788Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Special Features:
Round flatted threaded and pin type shaft
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Test Data Document:
31349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No No
Fiig:
A052b0