

View Online at <https://aerobasegroup.com/nsn/5930-00-581-4116>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.437 inches

Body Length:

Between 1.234 inches and 1.266 inches

Body Width:

0.491 inches

Body Height:

Between 1.296 inches and 1.328 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.437 inches

Actuator Length:

Between 0.281 inches and 0.313 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.109 inches and 0.141 inches

Actuator Width:

Between 0.234 inches and 0.266 inches

Actuator Free Position Height:

Between 0.422 inches and 0.454 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

3 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

5.0 ounces

Switch Actuating Force:

45.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0