

View Online at <https://aerobasegroup.com/nsn/5930-00-581-4116>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

1.437 inches

**Body Length:**

Between 1.234 inches and 1.266 inches

**Body Width:**

0.491 inches

**Body Height:**

Between 1.296 inches and 1.328 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.437 inches

**Actuator Length:**

Between 0.281 inches and 0.313 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.109 inches and 0.141 inches

**Actuator Width:**

Between 0.234 inches and 0.266 inches

**Actuator Free Position Height:**

Between 0.422 inches and 0.454 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

3 two circuit, double break/double make, both positions maintained single switch unit

**Switch Release Force:**

5.0 ounces

**Switch Actuating Force:**

45.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0