NSN 5930-00-581-4564



Lever Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-581-4564 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 2.062 inches **Overall Height:** 4.531 inches **Overall Width:** 1.250 inches **Bushing Length:** Between 0.344 inches and 0.406 inches **Body Length:** 2.406 inches **Body Width:** Between 1.219 inches and 1.281 inches **Body Height:** 2.062 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.407 inches and 0.469 inches **Actuator Height:** Between 1.156 inches and 1.656 inches **Actuator Position-action Relationship:** Up position maintained and down position momentary **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 125.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 20 **Pile-up Contact Form Arrangement:**

2a2b 2nd position **Thread Size:**

0.500 inches

NSN 5930-00-581-4564

Lever Switch - Page 2 of 2



Contact Load Current Rating	At Maximum	Rated Voltage:
5 000 amperes resistive ac		

Thread Series Designator:

Unf

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0