# NSN 5930-00-581-4564

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-581-4564

# Thread Class:

2a

Body Style:

Bushing mounted

## Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.062 inches

#### **Overall Height:**

4.531 inches

#### **Overall Width:**

1.250 inches

#### **Bushing Length:**

Between 0.344 inches and 0.406 inches

#### **Body Length:**

2.406 inches

#### Body Width:

Between 1.219 inches and 1.281 inches

#### **Body Height:**

2.062 inches

## Actuator Style:

Round

#### Actuator Diameter:

Between 0.407 inches and 0.469 inches

#### **Actuator Height:**

Between 1.156 inches and 1.656 inches

## Actuator Position-action Relationship:

Up position maintained and down position momentary

#### Actuator Color:

Black single actuator

#### Maximum Voltage Rating In Volts:

125.0 ac

# Inclosure Type:

Uninclosed

# Mounting Method:

Threaded bushing

# Thready Qty Per Inch (tpi):

20

# Pile-up Contact Form Arrangement:

2a2b 2nd position

# Thread Size:

0.500 inches

# NSN 5930-00-581-4564

Lever Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

#### **Thread Series Designator:**

Unf

# Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A053a0