

View Online at <https://aerobasegroup.com/nsn/5930-00-581-4889>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.125 inches

Overall Height:

3.000 inches

Overall Width:

3.625 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

20.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.20/+15.00 actuation point pounds per square inch

Contact Stimulus Rating:

70.00 differential point pounds per square inch and 80.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0