Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-581-6034

Wa	atertight
	verall Height:
	.875 inches
Οv	verall Width:
6.3	312 inches
Sh	aft Length:
1.0	094 inches single actuator
Un	threaded Mounting Hole Diameter:
0.5	531 inches single mounting facility
Inc	dividual Section Quantity:
15	
Kn	ob Manufacturer Code:
80	064
Kn	ob Manufacturer Part Number:
90	00s6202-73075pc1
Lo	ngest Horizontal Distance Between Mounting Centers:
7.8	375 inches single mounting facility
Lo	ngest Vertical Distance Between Mounting Centers:
4.1	25 inches single mounting facility
Sw	vitch Contact Basic Design:
No	onpile-up symmetrical
Мс	ounting Method:
Bra	acket single mounting facility
Fe	atures Provided:
Ac	tuator knob and metallic inclosure
Co	ontact Voltage Rating In Volts:
12	5.0 ac at sea level
Mo	ounting Facility Pattern:
Fo	ur position rectangular single mounting facility
Sw	vitch Actuator Indexing Position Quantity:
8 s	single actuator
Sh	aft Type:
Re	ectangular/square, threaded hole single actuator
Sq	uare Shaft Size:
0.2	248 inches single actuator
Те	rminal Type:
Та	b w/screw
Co	ontact Switching Action:
Bre	eaks before makes each section front
Sv	vitch Actuator Positioning Increment:
	.0 degrees single actuator

NSN 5930-00-581-6034

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Test Data Document:

80064-9s5564l drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Or Standard:

4jrbb style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0