

View Online at <https://aerobasegroup.com/nsn/5930-00-581-6037>

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

17.000 inches

Overall Width:

6.312 inches

Shaft Length:

1.094 inches single actuator

Unthreaded Mounting Hole Diameter:

0.531 inches single mounting facility

Individual Section Quantity:

10

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6202-73075pc1

Longest Horizontal Distance Between Mounting Centers:

7.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

4.125 inches single mounting facility

End Application:

Ticonderoga class cg

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.248 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Miniature panel mount

Test Data Document:

80064-9s5564I drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Specification Or Standard:

2jrbb style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0