## NSN 5930-00-581-6566

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-581-6566

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
4.750 inches
Overall Height:
2.906 inches
Overall Width:
2.813 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
G
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
<b>Shortest Horizontal Distance Between Mounting Centers:</b>
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
2 single section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
3 single actuator
Terminal Type:
Screw
Contact Switching Action:

Breaks before makes single section front

## NSN 5930-00-581-6566

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0