

View Online at <https://aerobasegroup.com/nsn/5930-00-581-6887>

Inside Diameter:

0.250 inches single connection

Overall Length:

5.562 inches

Overall Height:

2.875 inches

Overall Width:

5.875 inches

Body Length:

2.500 inches

Body Width:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

20.00 inches of water

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

7.4 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.30/+3.00 actuation point inches of water and +0.30/+3.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

115.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0