NSN 5930-00-581-8243

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:

Dustproof

1.000 inches

Bushing/hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-581-8243

Center To Center Distance Between Mounting Facilities Parallel To Length:

Bushing Length:
0.270 inches
Body Length:
1.812 inches
Body Width:
0.640 inches
Body Height:
0.640 inches
Unthreaded Mounting Hole Diameter:
0.145 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.675 inches
Actuator Free Position Height:
0.500 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
3.0 ounces
Switch Actuating Force:
20.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.100 overtravel inches and 0.015 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug

NSN 5930-00-581-8243

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0