

View Online at <https://aerobasegroup.com/nsn/5930-00-581-8626>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.235 inches single mounting facility and 0.265 inches single mounting facility

**Overall Length:**

1.531 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.735 inches single actuator and 0.765 inches single actuator

**Overall Diameter:**

Between 1.235 inches and 1.265 inches

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**End Application:**

Strategic weapon systems (poseidon & trident); missile, air-to-air, phoenix (aim-54); missile, all weather anti-ship, harpoon (agm-84)

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0