

View Online at <https://aerobasegroup.com/nsn/5930-00-581-8626>

Thread Class:

2a single mounting facility

Thread Length:

0.235 inches single mounting facility and 0.265 inches single mounting facility

Overall Length:

1.531 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.735 inches single actuator and 0.765 inches single actuator

Overall Diameter:

Between 1.235 inches and 1.265 inches

Individual Section Quantity:

1

Operating Temperature Range:

-25.0/+85.0 degrees celsius

End Application:

Strategic weapon systems (poseidon & trident); missile, air-to-air, phoenix (aim-54); missile, all weather anti-ship, harpoon (agm-84)

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0