

View Online at <https://aerobasegroup.com/nsn/5930-00-583-1257>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

0.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Height:**

0.537 inches

**Overall Width:**

0.250 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.356 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.092 inches

**Actuator Height:**

0.048 inches

**Actuator Free Position Height:**

0.350 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**End Application:**

Uh1/blackhawk/helo/elect countermeasure/ch 47/c141/los angeles/sturgeon/seawolf

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

4.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0