

View Online at <https://aerobasegroup.com/nsn/5930-00-583-1257>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.537 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.092 inches

Actuator Height:

0.048 inches

Actuator Free Position Height:

0.350 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

End Application:

Uh1/blackhawk/helo/elect countermeasure/ch 47/c141/los angeles/sturgeon/seawolf

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0