

View Online at <https://aerobasegroup.com/nsn/5930-00-583-1602>

Thread Class:

2a all threaded stud

Thread Length:

0.438 inches single pressure connection

Overall Length:

2.594 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.422 inches

Overall Diameter:

2.156 inches

Distance Between Mounting Facility Centers:

1.063 inches

Pressure Switch Type:

Gage

Mounting Method:

Threaded stud

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches all threaded stud

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Threaded stud

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.00 actuation point pounds per square inch and 17.00 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

32.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0