

View Online at <https://aerobasegroup.com/nsn/5930-00-583-2296>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

4.875 inches

**Overall Height:**

1.875 inches

**Overall Width:**

1.625 inches

**First Flat Length:**

0.438 inches single actuator

**Flat Height:**

0.213 inches single actuator and 0.223 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

4 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0