NSN 5930-00-583-2705

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-583-2705

Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
0.950 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.950 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.188 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

1.5 ounces

6.0 ounces

Actuator Movement:

Switch Actuating Force:

Between 0.075 pretravel inches and 0.094 overtravel inches and 0.020 differential inches

NSN 5930-00-583-2705

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

•

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0