NSN 5930-00-583-5927

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-583-5927

View Online at https://aerobasegroup.com/nsn/5930
Thread Length:
0.375 inches single mounting facility
Overall Length:
4.315 inches
Overall Height:
1.484 inches
Overall Width:
1.438 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
2.250 inches single actuator
Nonturn Device Radius:
0.438 inches at 9: 00 o'clock
Individual Section Quantity:
3
Knob Manufacturer Code:
71590
Knob Manufacturer Part Number:
P-120
Nonturn Device Type:
Tab at 9: 00 o'clock
Operating Tempurature Range:
-65.0/+175.0 degrees celsius
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Actuator knob
Thread Size:
Thread Size: 0.375 inches single mounting facility
044 0.20
0.375 inches single mounting facility
0.375 inches single mounting facility Contact Voltage Rating In Volts:
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity:
 0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity: 5 single actuator
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity: 5 single actuator Shaft Type:
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity: 5 single actuator Shaft Type: Round single actuator
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity: 5 single actuator Shaft Type: Round single actuator Terminal Type:
0.375 inches single mounting facility Contact Voltage Rating In Volts: 6.0 lowest dc voltage rating at sea level Switch Actuator Indexing Position Quantity: 5 single actuator Shaft Type: Round single actuator Terminal Type: Tab, solder lug

Adjustable stop single actuator

NSN 5930-00-583-5927

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guireiii	naumu.

5.5 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Reference Number Differentiating Characteristics:

As differentiated by sectional type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0