

View Online at <https://aerobasegroup.com/nsn/5930-00-583-6509>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.124 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.562 inches single actuator

Overall Diameter:

1.031 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0