

View Online at <https://aerobasegroup.com/nsn/5930-00-583-6582>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.365 inches and 0.385 inches

Overall Height:

Between 0.479 inches and 0.499 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.346 inches and 0.366 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.087 inches and 0.097 inches

Actuator Height:

0.020 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0