NSN 5930-00-583-6705

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-583-6705

28.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
1 two circuit, double break/double make, both positions maintained Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Contact Load Current Rating At Maximum Rated Voltage: 8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
8.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	single switch unit
Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Shelf Life: N/a Unit Of Measure: Demilitarization: No	
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	
Demilitarization: No	
No	
No	
	
Fiig:	
A053a0	