

View Online at <https://aerobasegroup.com/nsn/5930-00-583-6706>

Thread Class:

2a

Body Style:

Bushing mounted

Bushing Length:

0.310 inches

Body Length:

0.780 inches

Body Width:

0.656 inches

Body Height:

1.000 inches

Actuator Diameter:

0.323 inches

Actuator Height:

0.440 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

230.0 ac and 30.0 dc

End Application:

Deep submergence systems program (dssp), emory s.Land class as, los angeles class ssn (637), air compressors high pressure, kidd class ddg, wichita class aor, spruance class dd (963) , forrestal class cv.

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0