NSN 5930-00-583-6707

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-583-6707

Maximum Voltage Rating In Volts: 28.0 dc Inclosure Type: Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Fully enclosed Thready Qty Per Inch (tpi): 32 Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Thread Size: 0.469 inches Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Nonpile-up Contact Arrangement: 1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
1 two circuit, double break/double make, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Contact Load Current Rating At Maximum Rated Voltage: 10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
10.000 amperes resistive dc Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Thread Series Designator: Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Uns Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
4 tab, solder lug Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0