

View Online at <https://aerobasegroup.com/nsn/5930-00-583-7921>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

Between 4.938 inches and 5.062 inches

Overall Height:

1.936 inches

Overall Width:

2.406 inches

Body Length:

Between 3.594 inches and 3.718 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Mounting Facility Centers:

1.562 inches

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between -75.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+25.00/+225.00 actuation point degrees fahrenheit and +25.00/+225.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0