

View Online at <https://aerobasegroup.com/nsn/5930-00-583-7921>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

Between 4.938 inches and 5.062 inches

**Overall Height:**

1.936 inches

**Overall Width:**

2.406 inches

**Body Length:**

Between 3.594 inches and 3.718 inches

**Unthreaded Mounting Hole Diameter:**

0.187 inches

**Distance Between Mounting Facility Centers:**

1.562 inches

**Temperature Sensing Element Type:**

Bulb

**Operating Temperature Rating:**

Between -75.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+25.00/+225.00 actuation point degrees fahrenheit and +25.00/+225.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0